

Corporate Headquarters
4501 Parkway
Commerce Boulevard
Orlando, Florida USA 32808
(407) 578-8007
Fax (407) 578-8377
<http://www.datamaxcorp.com>

Datamax International
Herbert House
Elizabeth Way, Pinnacles
Harlow, Essex CM19 5FE UK
+44 1279 772200
Fax +44 1279 424448

Datamax Latin America
4501 Parkway
Commerce Boulevard
Orlando, Florida USA 32808
(407) 523-5520
Fax (407) 578-8377

Asia-Pacific Sales
19 Loyang Way
#01-01 CILC Building
Singapore 508724
+65 542-2611
Fax +65 542-3611

	I-4208	I-4308	I-4212	I-4406	I-4604
PRINT SPEED	8 IPS	8 IPS	12 IPS	6 IPS	4 IPS
RESOLUTION	203 DPI	300 DPI	203 DPI	406 DPI	600 DPI
PRINT WIDTH	4.10" (104 mm)	4.16" (105.7 mm)	4.10" (104 mm)	4.10" (104 mm)	4.16" (105.7mm)
PRINT LENGTH*	0.25" – 99" (6.35mm – 2475.6mm)	0.25" – 99" (6.35mm – 2475.6mm)	0.25" – 99" (6.35mm – 2475.6mm)	0.25" – 84" (6.35mm – 2133.6mm)	0.25" – 55" (6.35mm – 1397.0mm)
MEMORY	1MB Flash; 8MB SDRAM	2MB Flash; 16MB SDRAM	2MB Flash; 16MB SDRAM	2MB Flash; 16MB SDRAM	2MB Flash; 16MB SDRAM

* Print length values vary with printer configuration

PRINTER TYPE	Direct Thermal, Optional Thermal Transfer
BAR CODE MODULUS	5 mil to 150 mil (203 dpi); 3.3 mil to 150 mil (300 dpi); 2.5 mil to 150 mil (406 dpi); 1.6 mil to 150 mil (600 dpi) "X" dimension in picket fence or ladder orientations
MEDIA WIDTH	1" – 4.65" (25.4mm – 118.11mm)
MEDIA TYPE	Roll-fed or fan-fold materials, die-cut or continuous labels; perforated or continuous tag/ticket stock
MEDIA THICKNESS	.0025" – .0100" (.0635mm – .254mm)
MEDIA SENSING	Adjustable sensor detects "see through" for liner-backed die-cut labels and tags or reflective sensing for media with black stripe sensing
SUPPLY ROLL	8" (203mm) maximum diameter on 1.5" – 3" (38mm – 76mm) core. Fan-fold stock accepted from rear of printer
REVOLVING MEDIA HUBS	Standard 3" and 1.5" hubs, optional 40mm
LABEL BACKFEED	For use with optional cutter
RIBBONS	Industry standard ribbon widths; 1" (25mm) ribbon core, 1968' (600M) in length
CABINET	Metal construction, clear side window to easily monitor media supply levels
BAR CODES	Code 3 of 9, UPC-A, UPC-E, Interleaved 2 of 5, Code 128, EAN-8, EAN-13, HIBC, Codabar, Plessey, UPC 2 and 5 digit addendums, Code 93, Postnet, UCC/EAN Code 128, Telepen, UPS MaxiCode, FIM, PDF417, USD-8, Datamatrix, QR Code, Aztec, TLC 39, Micro PDF417
RESIDENT FONTS	Ten alphanumeric fonts from .035" (.89mm) to .64" (16.26mm) including OCR-A, OCR-B, CG Triumvirate™, CG Triumvirate Bold Condensed™ scalable font from AGFA®.
DOWNLOADABLE FONT TYPES	True-Type, AGFA® Intellifont™, Bitmap
CHARACTER SET	Modified IBM® Code Page 850; includes characters for English and most European, Scandinavian and Spanish speaking countries
FONT EXPANSION/ROTATION	All fonts expandable vertically and horizontally up to 24x; fonts and graphics can be printed in four directions: 0°, 90°, 180° and 270°
GRAPHICS SUPPORTED	.PCX, .BMP and .IMG files
REVERSE FIELDS/MIRROR IMAGE	Any font or graphic field can be printed as a normal or reverse image
INTERFACES	Centronics® Parallel port, IEEE 1284 compliant and RS232 at 2,400 to 38,400 BPS; optional Ethernet, USB, and Twinax/Coax
WINDOWS® DRIVER	Used for creating label formats using virtually any Windows®-based program. Included on Datamax Accessories CD, or via our web site at www.datamaxcorp.com
POWER SOURCE	Auto-sensing 90 – 204 VAC @ 47 – 63 Hz; specify appropriate power cord when ordering
OPERATING TEMPERATURE	32°F to 100°F (0°C to 38°C)
DIMENSIONS	12.70" H x 12.62" W x 18.60" D (322.6mm H x 320.6mm W x 472.5mm D)
WEIGHT	45 lbs., 20.5Kg

DATAMAX I-CLASS OPTIONS:

- THERMAL TRANSFER
- PEEL AND PRESENT
- DMXnet ETHERNET CONNECTIVITY
- LIGHT DUTY CUTTER
- FONT EXPANSION CARD
- USB INTERFACE
- STANDARD CUTTER
- ILPC - CG TIMES™ FIRMWARE
- RS-422 INTERFACE*
- INTERNAL REWIND
- I/O EXPANSION CARD
- TWINAX / COAX INTERFACE
- LABEL PRESENT SENSOR
- LINEAR SCANNER
- HANGUL, SIMPLIFIED CHINESE, AND KANJI FONT SUPPORT

* Not available for the I-4208



Built to UL, CSA and TUV-GS safety standards, FCC Class A emissions standard and CE Mark. This data sheet is for informational purposes only. DATAMAX MAKES NO WARRANTIES, EXPRESSED OR IMPLIED IN THIS SUMMARY. Specifications are subject to change without notice. All trademarks are the property of their respective owners. ©2003 DATAMAX BAR CODE PRODUCTS CORPORATION. All rights reserved. Datamax is an ISO 9001 registered company.